

The HTW gasification technology and its application to solid waste materials

PD Dr. Dobrin Toporov and
Dr. Elyas Moghaddam

GIDARA[®]
ENERGY


Who we are

GIDARA[®]
ENERGY

HTW[®] Technology



Simulation & Experiment for HTW[®]2.0 Design




Advanced Methanol Amsterdam & Rotterdam Plants



GIDARA Energy structure

GIDARA is jointly owned by **Ara partners**, US private equity firm, and **G.I. Dynamics**, Dutch engineering and project development firm, for the sole purpose of building Renewable Gasification to (Bio-)Fuel plants.



Ability to Convert Wide Range of Feedstock into High Value Products

Material Feedstock Flexibility

- Wood Waste 
- Sewage Sludge 
- Municipal Solid Waste 
- Non-Recyclable Plastics 
- Waste Paper 
- Agricultural Residue 
- Construction & Demolition Waste 

Adaptable and Cost-Effective Gasification Technology



GIDARA Energy's process and commercially proven & mature HTW[®] technology plus adapted purification design allows a broad range of feedstocks (with minor to no incremental CAPEX)

Multiple End Product Applications

Road Transport Fuels

- Green Gasoline
- Biomethanol
- Renewable Diesel
- Green H₂
- Renewable Natural Gas (CNG, LNG)
- Bio-mmtpa



Marine Fuels

- Biomethanol
- Bio-Ammonia
- Bio-DME
- Renewable Natural Gas (CNG, LNG)



Sustainable Aviation Fuels

High Growth End Markets (e.g. Chemicals)



Technology proven and applied for more than 10 yrs and with wide range of feedstock

- ✓ Experience in pressurized fluidized bed gasification since 1978
- ✓ + 600 Mio Euro: - Investment in development of HTW till 2022
- ✓ 3 commercial plants: - Successfully built and operated
- ✓ +10 years: - Operational time of a single plant.
- ✓ +91% Availability: - Average availability in 10 year
- ✓ +5% Extra availability: - Can be increased by process improvements
- ✓ Existing Testing facility: - Recent successful test on all mixtures of RDF and biomass waste

Key reference plant

1986 - 1997



Commercial plant
at Berrenrath, Germany



Purpose/learnings of the plant

- ✓ Methanol production from syngas
- ✓ Long-term use of RDF + plastic sources, feedstock flexibility
- ✓ Pressure range 10 bar

1988 - 1994



Commercial plant
at Oulu, Finland



Purpose/learnings of the plant

- ✓ Produce ammonia from syngas
- ✓ Utilisation of peat and waste wood as feedstock, feedstock flexibility
- ✓ Pressure range 10 bar

1989 - 1992



High pressure plant
at Wesseling, Germany



Purpose/learnings of the plant

- ✓ Sustainable HTW gasification operations under 25 bar

1999 - 2002



Demonstration plant
at Niihama, Japan



Purpose/learnings of the plant

- ✓ Utilizing direct municipal solid waste as feedstock to produce syngas

Key reference plant

2020 - current



Demonstration plant
at TU Darmstadt, Germany



Purpose/learnings of the plant


- ✓ Feedstock testing and continuous research and development on HTW technology
- ✓ Full production including methanol

Today

Proven track record of multiple HTW projects, strong market demand and regulatory tailwinds make HTW technology an economically viable option for biofuels


1970s

Rheinbraun & ThyssenKrupp developed the pressurized version of the gasifier known as the High Temperature Winkler (HTW) process




Superiority of HTW[®] 2.0 Gasification Technology

- **Less O₂ consumption** compared to Entrained flow gasification process;
- High flexibility for **operational load** over a wide range of operating conds.;
- **Simple** start-up and shut-down procedures;
- **No undesired by-products** in the syngas, incl. tars: phenols and HMW hydrocarbon;
- **Proven and robust sub-systems** such as: feeding system, waste heat recovery, dry dust removal



HTW[®]2.0 Fluidized Bed Gasifier

- Pressurized Bubbling Fluidized Bed
- Agents: Air or O₂, Steam and CO₂
- Injected via nozzles at several levels along the Gasifier
- Thermal zones: Fluidized Bed: 750-1000 °C
Freeboard: 900-1200 °C
- Pressure: 1-30 bar (40 bar technically feasible)
- Feedstock rate: up to 160 t/h
- Carbon Conversion: over 95%
- High Cold Gas Efficiency (over 85%)
- Designed availability: 8000 h/y (approx. 91%)
- Proven experience with wide range of feedstock incl. low rank coal, biomass, MSW-driven wastes (RDF, SRF), sewage sludge, peat, etc.



Experience from Key Reference Plant (Berrenrath-Germany)

HTW™-to-Methanol Plant (10 bar, 720 tpd) – HTW™ Unit

Feed:	25 t/h
Operating pressure:	10 bar
Syngas (CO+H ₂) production:	38,000 Nm ³ /h
Cold gas efficiency:	85 %
Carbon conversion:	95 %
In operation:	1986 - 1998
Methanol Production:	300 tpd
Total operation:	76,000 h
RDF*:	15,195 h
Type of feedstock used:	lignite, DSD-plastic residue, sewage sludge, SRF, Waste Wood, Dioxin /furan-loaded cokes from waste incineration

*Excluding other waste combinations such as sewage sludge, wood, peat, etc.



HTW Demonstration Plant
Berrenrath (1986-1997)

26/04/2023

GIDARA
ENERGY

Experience from Key Reference Plant (Berrenrath-Germany)

HTW™-to-Methanol Plant (10 bar, 720 tpd) – HTW™ Unit

- Syngas Quality:

H₂O 17.5 vol%

CH₄ 3.3 vol%

CO 31.6 vol%

CO₂ 18.2 vol%

H₂ 29.2 vol%

N₂ 0.2 vol%


H₂S 560 ppm

- Specific Oxygen Consumption:

O₂ Nm³/kg coal, daf – 0.39

- Specific Syngas Production:

CO+H₂ – 1500 Nm³ /t brown coal, daf




HTW Demonstration Plant
Berrenrath (1986-1997)

Experience from Key Reference Plant (Berrenrath-Germany)

HTW™-to-Methanol Plant (10 bar, 720 tpd) – Essential Components and Process Steps

- Dried brown coal entry via 3-lock hopper system by means of screws and/or pneumatic conveying,
- Gasification at 10 bar with O₂/steam and some recycled CO₂,
- Raw gas cooling by water tube and fire tube cooler in series,
- Dry de-dusting using ceramic filter candles in a warm gas filter unit at approx. 270°C,
- Water scrubbing to remove ammonia and chlorine, contribute to water vapor saturation at approx. 130°C and as a protective device against dust penetration for the downstream catalysts.
- Sulfur-resistant CO conversion and HCN/COS hydrolysis,
- Converted gas compression to approx. 37 bar,
- Rectisol scrubbing for H₂S and CO₂ removal,
- Delivery of synthesis gas via pipeline to DEA Wesseling
- Sour gas treatment to process CO₂ and elemental Sulphur.



Experience from Key Reference Plant (Berrenrath-Germany)

Waste co-gasification: DSD – plastic residual pellets

- **Short term tests** -> 2-days long test with 40% residual materials (9 t/h) have been carried out. To check the existing equipment and operation behavior.
- **Long-term tests** -> 1-year long tests with variation between 1-5 t/h DSD mixed plastics. (approx. 25% of total load)
To detect and eliminate weak points
- **Continuous operation** - with mostly 2-3 t/h DSD plastics. (approx. 15% of total load) in order to be able to keep the benzene within approved limits. (legal approval for up to 5 t/h DSD)
To improve profitability
- Total 25 000 tons

Year	In operation	Coal + Coke + MSW	Plastic Waste	O2 consumed	Syngas produced	Syngas delivered for MeOH production
	hours	t	t	10 ³ m ³	10 ³ m ³	10 ³ m ³
1986**	3 068	60 189		19 500	47 186	29 360
1987**	3 732	90 844		31 292	116 069	98 833
1988**	5 878	150 396		52 467	195 951	187 402
1989	7 394	170 656		60 923	242 666	239 029
1990	5 897	144 433		49 991	200 700	197 657
1991	6 929	161 519		55 556	224 553	221 413
1992	6 821	168 262		56 634	231 725	231 710
1993	7 984	127 325	676	43 613	175 391	172 092
1994	7 668	158 722	3 295	55 680	223 700	221 747
1995	6 295	94 954	4 372	31 440	129 573	126 807
1996	7 307	124 839	6 283	45 629	183 003	177 385
1997	7 528	104 453	10 142	39 373	160 274	154 055
Total	76 500	1 556 592	24 731	542 097	2 130 791	2 057 489

Experience from Key Reference Plant (Berrenrath-Germany)


Waste co-gasification: various waste materials

- **Dried sewage sludge** - tests were carried out in the summer of 1993 and in autumn 1994. A total of 504 t of dried municipal sewage sludge with admixing rates of 3-5 t / h were used.
- **Loaded cokes** - In a series of tests in 1997, about 400 t of coke from flue gas cleaning systems of MSW incinerators in Kassel and Rotterdam was gasified
- **SRF pellets** - In the autumn of 1997, in the framework of EU-Thermie Project, around 1,050 t of processed municipal solid waste were gasified together with brown coal.
- **Waste Wood** – tests with approx. 21 t of shredded waste wood were performed. A conveyance experiment with wood only in a cold system showed that the pressurization in a lock hopping system is problematic due to the building of bridges and holes in the vessels. Thus, for mono-gasification of wood in pressurized systems, it is recommended to take some pre-treatment steps of the wood (such as palletization, for instance).

Experience from Key Reference Plant (Berrenrath-Germany)


Waste co-gasification: Summary

- pre-treatment/upgrade of MSW to SRF and RDF, make them a suitable feedstock for HTW™ process;
- Trouble-free storage, conveying and feeding under pressure of RDF pellets into HTW gasifier;
- No adverse effect on operation of gasifier and downstream processes
- No significant change in syngas composition;
- Insensitivity of the HTW process to fluctuations in the calorific value of the raw materials
- Emission limits are met successfully;
- Dioxins and furans are destroyed by gasification effectively. No dioxins can be formed in gasifier (no oxygen)



Development of GIDARA Energy's Fluidized bed Gasification Process to HTW® 2.0

- Upgraded to the technological and environmental standards of today
- Adapting with 100% non-recyclables as feedstock
- Improving/Modernizing feeding line and BOP and dust removal system
- Implementing advanced design for raw gas cooling system



HTW® Pilot Plant in operation since 2015


R&D facility at TU Darmstadt (Energy Systems and Technology)

Key operating parameters

- Thermal Input: 500 kWth
- Gasification temperatures
 - Fluidized bed: 700 - 900 C
 - Free board: 800 - 1200 C
- Gasifier dimensions:
 - Height: 12 m
 - Diameter: 1 m
- Designed for long term tests of diff. feedstock
- Definition of key design and operational parameters
- Further process enhancement



HTW: Pilot Plant at TU-Darmstadt



- (a) gasifier;
- (b) screw conveyer;
- (c) bottom product discharge;
- (d) raw gas cooler;
- (e) hot gas filter;
- (f) syngas ventilator;
- (g) thermal post combustor;
- (h) fresh air ventilator;
- (1) online moisture measurement;
- (2) online gas analysis;
- (3) bed inventory;
- (4) tar measurement;
- (5) gas sample bags;
- (6) dust

Cooperation with TU Darmstadt: Continued long-term Feedstock Testing



April 27th, 2020

100% FW pellets
100% RDF pellets } Mixing

May 8th, 2021




PFM: 75% RDF – 25% WW

Nov. 2022

100% WW pellets
75% WW pellets + 25% RDF pellets

June 2023


Planned test for:
75% WW pellets } Mixing
25% RDF pellets



- 2 main targets:
- To test new RDF pellets
 - To test new feedstocks:
Peanut shell pellets
Sunflower husk pellets

Flagship Facility “Advanced Methanol Amsterdam (AMA)”

HTW™-to-BioMethanol Plant: Process Flow Diagram





#	Interface
1	PARO supplying waste wood and RDF
2	Pelletizing Company with conveying line to Gasifier
3	Methanol
4	Blended fuel – RED II requirement for bp
5	Dust and bottom product to cement industry
6	Linde/OCAP to export CO2
7	Power supply

Flagship Facility “Advanced Methanol Amsterdam (AMA)” HTW™-to-BioMethanol Plant (15 bar, 530 tpd) – HTW™ Section

Feed:	22 t/h
Operating pressure:	15 bar
Raw Syngas production:	41,000 Nm ³ /h
Cold gas efficiency:	> 80 %
Carbon conversion:	95 %
In operation:	2025
Bio-Methanol Production:	260 mtpd
Type of feedstock to be used:	RDF pellets and Waste Wood pellets



Advanced Methanol
Amsterdam Plant



Twin facilities

Amsterdam



ADVANCED METHANOL



Rotterdam

Concluding Remarks

- GIDARA's goal is to meet the demand for cleaner fuels
 - address the waste challenges,
 - reduce global carbon emissions and
 - contribute to more circular economy;
- GIDARA has acquired the commercially proven HTW™ gasification technology;
- Ongoing R&D program focused on:
 - long-term pilot tests of different feedstock to define key-operating gasification parameters and to demonstrate the flexibility of HTW® for a variety of feedstock
 - further improvement of in-house numerical tools developed for modeling and design of HTW® gasification process
- GIDARA Energy is currently building its commercial flagship facilities “Advanced Methanol Amsterdam (AMA)” and Advanced Methanol Rotterdam (AMR)” that convert RDF and Waste Wood into advanced Bio-Methanol.

Thank you!

Dr. Dobrin Toporov

Dr. Elyas Moghaddam

M: +31 (0)6 16339524

P: +31 (0)158200700

E: e.moghaddam@gidynamics.nl

GIDARA[®]
ENERGY

Copyright

Copyright of all published material including photographs, drawings and images in this document remains vested in GIDARA Energy and third party contributors as appropriate. Accordingly, neither the whole nor any part of this document shall be reproduced in any form nor used in any manner without express prior permission and applicable acknowledgements. No trademark, copyright or other notice shall be altered or removed from any reproduction.

Disclaimer

This Presentation includes and is based, inter alia, on forward-looking information and statements that are subject to risks and uncertainties that could cause actual results to differ. These statements and this Presentation are based on current expectations, estimates and projections about global economic conditions, the economic conditions of the regions and industries that are major markets for GIDARA Energy and its (including subsidiaries and affiliates) lines of business. These expectations, estimates and projections are generally identifiable by statements containing words such as “expects”, “believes”, “estimates” or similar expressions. Important factors that could cause actual results to differ materially from those expectations include, among others, economic and market conditions in the geographic areas and industries that are or will be major markets for GIDARA Energy’s businesses, oil prices, market acceptance of new products and services, changes in governmental regulations, interest rates, fluctuations in currency exchange rates and such other factors as may be discussed from time to time in the Presentation. Although GIDARA Energy believes that its expectations and the Presentation are based upon reasonable assumptions, it can give no assurance that those expectations will be achieved or that the actual results will be as set out in the Presentation. GIDARA Energy is making no representation or warranty, expressed or implied, as to the accuracy, reliability or completeness of the Presentation, and neither GIDARA Energy nor any of its directors, officers or employees will have any liability to you or any other persons resulting from your use. GIDARA Energy is used as the common brand or trade mark for most of these entities. In this presentation we may sometimes use “GIDARA Energy BV”, “GID”, “we” or “us” when we refer to GIDARA Energy in general or where no useful purpose is served by identifying any particular GIDARA Energy company.